

IW-12.8V 100Ah

LITHIUM IRON PHOSPHATE BATTERY



High cycle life
>3000 cycles @80%
DOD for effectively
lower total cost of
ownership.



Longer service life
Stable,
low- maintenance
batteries with smart
SOC monitoring.



**Built in circuit
protection**
BMS are incorporated
against abuse.



Quickly recharge
Superior charge-
discharge efficiency
minimizes downtime
for higher
productivity.



**Extreme heat
tolerance**
Reliable up to +60 ° C,
ideal for
high- temperature
scenarios.

DATASHEET

ELECTRICAL PERFORMANCE	
Nominal Voltage	12.8 V
Nominal Capacity	100 Ah
Capacity @ 20A	300 min
Energy	1280 Wh
Resistance	$\leq 20 \text{ m}\Omega$ @ 50% SOC
Self Discharge	<3% / Month
Cells	Prismatic Cell 100Ah
CHARGE PERFORMANCE	
Recommended Charge Current	20 A
Maximum Charge Current	50 A
Recommended Charge Voltage	14.6 V
Charge Cut-Off Voltage	<15.2 V (0.5 ~ 1.5 s)
Reconnect Voltage	>14.4 V
Balancing Voltage	<14 V
Maximum Batteries in Parallel	4
DISCHARGE PERFORMANCE	
Maximum continuous Discharge Current	150A
Peak Discharge Cut-Off Current	450A (200~500ms)
Discharge Cut-Off Voltage	10V (2000 ms)
Reconnect Voltage	>11.2V
Short Circuit Protection	1000-2000A+ 400A(200 ~ 800 μ s)
TEMPERATURE PERFORMANCE	
Discharge Temperature	-20~75° C
Charge Temperature	0~50° C
Storage Temperature	-5~35° C
DIMENSION	
Dimensions	L330 *W172*H215mm
MECHANICAL PERFORMANCE	
Weight	11.5kg
Terminal Type	M8
Terminal Torque	80~100 in-lbs (9~11 N-m)
Case Material	ABS
Ingress Protection Code	IP65
Bluetooth	Bluetooth 4.0 with smartphone App
Weight	11.5kg
COMPLIANCE	
Certifications	CE, UN38.3, UL1642 & IEC62133
Shipping Classification	UN 3480, CLASS 9

This material is for reference only and does not constitute any commitment regarding product performance or specifications. Product design and specifications may be changed at any time.

The Company assumes no liability for any losses arising from the use of this material or the products